

## EMBLEM Latex-UV Wall Decoration 130 Neo

EMBLEM Latex-UV Wall Decoration 130 Neo is a paper-based non-woven wallpaper for individual interior design. The soft, matt, neutral white surface of the non-woven wallpaper can be printed with common latex and UVC inks. The EMBLEM LUVWADE130N is processed like standard non-woven wallpapers.

Matchcode:	<b>LUVWADE130N</b>
Material:	coated paper fleece, free from glass fibres
Finish:	matt
Color:	white
Weight:	130 g/m <sup>2</sup>
Thickness:	190 µm
Opacity:	n.n.
Application temperature:	more than 15 °C
Fire behaviour:	not certified
Standard rolls width:	800 / 1600 mm
Standard roll length:	80 m
Storage:	cool and dry environment, at 15 - 25 °C, 50 % rel. humidity
Shelf life:	12 month in original packing

### COMPATIBLE INKS:

Eco Solvent:	no	UVC:	yes
Solvent:	no	Latex:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

## EMBLEM Latex-UV Wall Decoration 130 Neo

### Description:

EMBLEM Latex-UV Wall Decoration 130 Neo is a paper-based non-woven wallpaper for individual interior design. The matt, neutral white surface of the non-woven wallpaper can be printed with common latex and UVC inks. The wallpaper has a pleasantly soft feel and a noticeable non-woven structure that gives it a high sense of value.

High-quality prints in photo-realistic quality can be produced on the LUVWADE130N. It is free of PVC, plasticisers and solvents, without the addition of heavy metal compounds and formaldehyde. EMBLEM LUVWADE130 has a high opacity and is crack-bridging. It is easy to apply. The wallpaper adheres to smooth, slightly rough wall surfaces or plasters painted with binder paint. It can also be easily removed dry.

From an ecological point of view, LUVWADE130N is very environmentally friendly, PVC-free and made from regrowing raw materials.

### Processing:

The prints can be used un laminated indoors as decoration.

For further processing as decorative wallpaper, the usual procedures for wallpapering apply. The substrate must be dry, clean, firm, absorbent and smooth. The wallpaper is usually applied using the wall pasting technique, in which the wall is pasted. If there are several panels, they are glued edge to edge. If necessary, a double seam cut can be made when the wall is dry. Press down the panels with a foam rubber roller or wallpaper brush until bubble-free. Remove escaping adhesive immediately with a damp cloth or sponge.

For applying the wallpaper, we recommend commercially available paste for non-woven paper wallpapers such as Metylan Direct for non-woven wallpapers.

### Application:

Typical applications for EMBLEM LUVWADE130 are individual room designs for living spaces, children's rooms, shopping centres, museums, trade fair construction, commercial spaces, hotels and restaurants.