

## Safety Data Sheet

according to UK REACH Regulation

### Ceramic Coating

Revision date: 17.05.2022

Product code: 359500018

Page 1 of 15

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Ceramic Coating

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Plating agent

#### Uses advised against

Do not use for private purposes (household). Reserved for industrial and professional use.

### 1.3. Details of the supplier of the safety data sheet

Company name:	ORAFOL Europe GmbH	
	Germany	
Street:	Orafolstraße 1	
Place:	D-16515 Oranienburg	
Telephone:	+ 49 3301 864 0	Telefax: + 49 3301 864 100
e-mail:	msds@orafol.de	
Contact person:	EHSQ Department	
Internet:	www.orafol.com	

### 1.4. Emergency telephone number:

National Poison Information Service: In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### GB CLP Regulation

Flam. Liq. 3; H226  
 Acute Tox. 4; H302  
 Asp. Tox. 1; H304  
 Skin Corr. 1B; H314  
 Eye Dam. 1; H318  
 Skin Sens. 1; H317  
 STOT SE 3; H336  
 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### GB CLP Regulation

#### Hazard components for labelling

Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with n-butyl acetate  
 Distillates (petroleum), hydro-treated light; Kerosine - unspecified  
 3-aminopropyltriethoxysilane

Signal word: Danger

#### Pictograms:



#### Hazard statements

H226 Flammable liquid and vapour.

## Safety Data Sheet

according to UK REACH Regulation

### Ceramic Coating

Revision date: 17.05.2022

Product code: 359500018

Page 2 of 15

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification (GB CLP Regulation)	
112-07-2	2-butoxyethyl acetate, butylglycol acetate	40 - < 55 %
	203-933-3	607-038-00-2
	01-2119475112-47	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4; H332 H312 H302	
475645-84-2	Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with	25 - < 30 %
	640-361-7	
	Flam. Liq. 2, Acute Tox. 4, Skin Corr. 1B, STOT SE 3, Aquatic Chronic 3; H225 H302 H314 H336 H412	
123-86-4	n-butyl acetate	20 - < 25 %
	204-658-1	607-025-00-1
	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066	
64742-47-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified	15 - < 20 %
	265-149-8	649-422-00-2
	Asp. Tox. 1; H304	
71750-79-3	Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me	1 - < 5 %
	Skin Irrit. 2, Eye Dam. 1; H315 H318	
919-30-2	3-aminopropyltriethoxysilane	1 - < 5 %
	213-048-4	612-108-00-0
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A; H302 H314 H318 H317	
108-88-3	toluene	< 1 %
	203-625-9	601-021-00-3
	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412	

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to UK REACH Regulation

### Ceramic Coating

Revision date: 17.05.2022

Product code: 359500018

Page 3 of 15

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
112-07-2	203-933-3	2-butoxyethyl acetate, butylglycol acetate	40 - < 55 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 2,66 mg/l (dusts or mists); dermal: LD50 = ca. 1500 mg/kg; oral: LD50 = ca. 1880 mg/kg	
475645-84-2	640-361-7	Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with	25 - < 30 %
		oral: ATE = 500 mg/kg	
123-86-4	204-658-1	n-butyl acetate	20 - < 25 %
		inhalation: LC50 = > 6,6 mg/l (vapours); oral: LD50 = 14130 mg/kg	
64742-47-8	265-149-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified	15 - < 20 %
		inhalation: LC50 = > 5,28 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
919-30-2	213-048-4	3-aminopropyltriethoxysilane	1 - < 5 %
		oral: ATE = 500 mg/kg	
108-88-3	203-625-9	toluene	< 1 %
		inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg	

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### General information

First aider: Pay attention to self-protection!  
 Remove affected person from the danger area and lay down.  
 Remove contaminated, saturated clothing immediately.

###### After inhalation

Remove casualty to fresh air and keep warm and at rest.  
 Call a physician immediately.

###### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

###### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

###### After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink 1 glass of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

##### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

##### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

###### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

###### Unsuitable extinguishing media

Water.

## Safety Data Sheet

according to UK REACH Regulation

### Ceramic Coating

Revision date: 17.05.2022

Product code: 359500018

Page 4 of 15

#### **5.2. Special hazards arising from the substance or mixture**

Flammable Pyrolysis products, toxic

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

In case of fire may be liberated:

Nitrogen oxides (NOx)

Carbon monoxide

#### **5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

#### **Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

#### **6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

#### **6.3. Methods and material for containment and cleaning up**

##### **For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours are heavier than air, spread along floors and form explosive mixtures with air.

##### **Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

##### **Hints on joint storage**

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

## Safety Data Sheet

according to UK REACH Regulation

### Ceramic Coating

Revision date: 17.05.2022

Product code: 359500018

Page 5 of 15

#### 7.3. Specific end use(s)

Plating agent

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
112-07-2	2-Butoxyethyl acetate	20	133		TWA (8 h)	WEL
		50	332		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL

**Safety Data Sheet**

according to UK REACH Regulation

**Ceramic Coating**

Revision date: 17.05.2022

Product code: 359500018

Page 6 of 15

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
112-07-2	2-butoxyethyl acetate, butylglycol acetate			
Worker DNEL, acute		inhalation	local	333 mg/m <sup>3</sup>
Worker DNEL, acute		dermal	systemic	120 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	775 mg/m <sup>3</sup>
Consumer DNEL, acute		dermal	systemic	72 mg/kg bw/day
Consumer DNEL, acute		inhalation	systemic	499 mg/m <sup>3</sup>
Consumer DNEL, acute		oral	systemic	36 mg/kg bw/day
Consumer DNEL, acute		inhalation	local	200 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	102 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	80 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	8,6 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	169 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	133 mg/m <sup>3</sup>
123-86-4	n-butyl acetate			
Worker DNEL, long-term		inhalation	systemic	300 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	600 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	300 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	600 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	11 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	35,7 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	300 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	35,7 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	300 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	6 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	6 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	2 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	2 mg/kg bw/day
108-88-3	toluene			
Worker DNEL, long-term		inhalation	systemic	192 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	384 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	192 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	384 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	384 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	56,5 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	226 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	56,5 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	226 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	226 mg/kg bw/day

**Safety Data Sheet**

according to UK REACH Regulation

**Ceramic Coating**

Revision date: 17.05.2022

Product code: 359500018

Page 7 of 15

Consumer DNEL, long-term	oral	systemic	8,13 mg/kg bw/day
--------------------------	------	----------	----------------------

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
112-07-2	2-butoxyethyl acetate, butylglycol acetate	
Freshwater		0,304 mg/l
Freshwater (intermittent releases)		0,56 mg/l
Marine water		0,03 mg/l
Freshwater sediment		2,03 mg/kg
Marine sediment		0,203 mg/kg
Secondary poisoning		60 mg/kg
Micro-organisms in sewage treatment plants (STP)		90 mg/l
Soil		0,415 mg/kg
123-86-4	n-butyl acetate	
Freshwater		0,18 mg/l
Freshwater (intermittent releases)		0,36 mg/l
Marine water		0,018 mg/l
Freshwater sediment		0,981 mg/kg
Marine sediment		0,098 mg/kg
Micro-organisms in sewage treatment plants (STP)		35,6 mg/l
Soil		0,09 mg/kg
108-88-3	toluene	
Freshwater		0,68 mg/l
Freshwater (intermittent releases)		0,68 mg/l
Marine water		0,68 mg/l
Freshwater sediment		16,39 mg/kg
Marine sediment		16,39 mg/kg
Micro-organisms in sewage treatment plants (STP)		13,61 mg/l
Soil		2,89 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

**Individual protection measures, such as personal protective equipment**
**Eye/face protection**

Suitable eye protection: goggles.

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is

## Safety Data Sheet

according to UK REACH Regulation

### Ceramic Coating

Revision date: 17.05.2022

Product code: 359500018

Page 8 of 15

recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable gloves type: Butyl caoutchouc (butyl rubber)  
 Thickness of the glove material  $\geq 0,7$  mm  
 Breakthrough time:  $\geq 60$  min.

Unsuitable material: CR (polychloroprene, chloroprene rubber), NR (natural rubber, Natural latex), PVC (polyvinyl chloride)

#### Skin protection

Use of protective clothing.

#### Respiratory protection

Respiratory protection necessary at: high concentrations  
 Full-/half-/quarter-face masks (EN 136/140) Combination filtering device (EN 14387)  
 Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m<sup>3</sup> (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m<sup>3</sup> (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m<sup>3</sup> (1.0 % by vol.)

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless clear
Odour:	Ammonia

#### Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	120 °C
Flash point:	35 °C

#### Flammability

Solid/liquid:	not applicable
Gas:	not applicable

#### Explosive properties

The product is not: Explosive.

Lower explosion limits:	1,2 vol. %
Upper explosion limits:	8,4 vol. %
Auto-ignition temperature:	420 °C
Decomposition temperature:	not determined
pH-Value:	not determined

Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
-------------------	--

#### Solubility in other solvents

not determined

Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	11 hPa
Density (at 20 °C):	0,93 g/cm <sup>3</sup>
Relative vapour density:	not determined

**Safety Data Sheet**

according to UK REACH Regulation

**Ceramic Coating**

Revision date: 17.05.2022

Product code: 359500018

Page 9 of 15

**9.2. Other information****Information with regard to physical hazard classes**

Oxidizing properties

The product is not: oxidising.

**Other safety characteristics**

Solvent content:

60%

Solid content:

not determined

Evaporation rate:

not determined

**Further Information****SECTION 10: Stability and reactivity****10.1. Reactivity**

Flammable.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

No known hazardous decomposition products.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****ATEmix calculated**

ATE (oral) 1364,7 mg/kg

**Safety Data Sheet**

according to UK REACH Regulation

**Ceramic Coating**

Revision date: 17.05.2022

Product code: 359500018

Page 10 of 15

**Acute toxicity**

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
112-07-2	2-butoxyethyl acetate, butylglycol acetate				
	oral	LD50 mg/kg	ca. 1880	Rat	Study report (1963) OECD Guideline 401
	dermal	LD50 mg/kg	ca. 1500	Rabbit	Toxicol Appl Pharmac 51, 117-27 (1979) Modification of the Draize 1959 method u
	inhalation vapour	ATE	11 mg/l		
	inhalation (4 h) dust/mist	LC50	2,66 mg/l	Rat	
475645-84-2	Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with				
	oral	ATE mg/kg	500		
123-86-4	n-butyl acetate				
	oral	LD50 mg/kg	14130	Rat	Publication (1954) acute oral toxicity test
	inhalation (4 h) vapour	LC50 mg/l	> 6,6	Rat	Study report (1988) OECD Guideline 403
64742-47-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified				
	oral	LD50 mg/kg	> 5000	Rat	Study report (1992) EPA OTS 798.1175
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1992) EPA OTS 798.1100
	inhalation (4 h) vapour	LC50 mg/l	> 5,28	Rat	Study report (1987) OECD Guideline 403
919-30-2	3-aminopropyltriethoxysilane				
	oral	ATE mg/kg	500		
108-88-3	toluene				
	oral	LD50 mg/kg	5580	Rat	Toxicology 4, 5-15 (1975) EU Method B.1
	dermal	LD50 mg/kg	> 5000	Rabbit	American Industrial Hygiene Association Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50	28,1 mg/l	Rat	Study report (1980) OECD Guideline 403

**Further information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

**SECTION 12: Ecological information**
**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

**Safety Data Sheet**

according to UK REACH Regulation

**Ceramic Coating**

Revision date: 17.05.2022

Product code: 359500018

Page 11 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
112-07-2	2-butoxyethyl acetate, butylglycol acetate					
	Acute fish toxicity	LC50 > 20 - < 40 mg/l	96 h	Oncorhynchus mykiss	Toxicol Mech & meth 12, 255-63 (2002)	OECD Guideline 203
	Acute algae toxicity	ErC50 1570 mg/l	72 h	Pseudokirchneriella subcapitata	Toxicol Mech & meth 12, 255-63 (2002)	ISO 8692
	Acute crustacea toxicity	EC50 67,5 mg/l	48 h	Daphnia magna	Toxicol Mech & meth 12, 255-63 (2002)	ISO 6341
123-86-4	n-butyl acetate					
	Acute fish toxicity	LC50 18 mg/l	96 h	Pimephales promelas	Publication (1984)	OECD Guideline 203
	Acute crustacea toxicity	EC50 44 mg/l	48 h	Daphnia sp.	Publication (1959)	OECD Guideline 202
	Crustacea toxicity	NOEC 23,2 mg/l	21 d	Daphnia magna	Study report (2000)	OECD Guideline 211
64742-47-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified					
	Acute algae toxicity	ErC50 8,3 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201
	Acute crustacea toxicity	EC50 1,4 mg/l	48 h	Daphnia magna	Study report (1995)	OECD Guideline 202
108-88-3	toluene					
	Acute fish toxicity	LC50 5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Acute algae toxicity	ErC50 134 mg/l			GESTIS	
	Acute crustacea toxicity	EC50 3,78 mg/l	48 h			
	Fish toxicity	NOEC 1,39 mg/l	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Crustacea toxicity	NOEC 0,74 mg/l	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (	other: US EPA 600/4-91-003
	Acute bacteria toxicity	(EC50 84 mg/l)				

**12.2. Persistence and degradability**

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
112-07-2	2-butoxyethyl acetate, butylglycol acetate				
	OECD 301F	88%	28		
	Readily biodegradable (according to OECD criteria).				
108-88-3	toluene				
		86	20		
	Biodegradable.				

**12.3. Bioaccumulative potential**

The product has not been tested.

## Safety Data Sheet

according to UK REACH Regulation

### Ceramic Coating

Revision date: 17.05.2022

Product code: 359500018

Page 12 of 15

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
112-07-2	2-butoxyethyl acetate, butylglycol acetate	1,51
123-86-4	n-butyl acetate	200
108-88-3	toluene	2,73

#### BCF

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).

#### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

##### List of Wastes Code - residues/unused products

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08); waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures; hazardous waste

##### List of Wastes Code - contaminated packaging

150107 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); glass packaging

##### Contaminated packaging

Hazardous waste according to Directive 2008/98/EC (waste framework directive). Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

##### 14.1. UN number or ID number:

UN 2924

##### 14.2. UN proper shipping name:

FLAMMABLE LIQUID, CORROSIVE, N.O.S.

##### 14.3. Transport hazard class(es):

3

##### 14.4. Packing group:

II

Hazard label:

3+8



**Safety Data Sheet**

according to UK REACH Regulation

**Ceramic Coating**

Revision date: 17.05.2022

Product code: 359500018

Page 13 of 15

Classification code: FC  
 Special Provisions: 274  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 Transport category: 2  
 Hazard No: 338  
 Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

14.1. UN number or ID number: UN 2924  
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S.  
14.3. Transport hazard class(es): 3  
14.4. Packing group: II  
 Hazard label: 3+8



Classification code: FC  
 Special Provisions: 274  
 Limited quantity: 1 L  
 Excepted quantity: E2

**Marine transport (IMDG)**

14.1. UN number or ID number: UN 2924  
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S.  
14.3. Transport hazard class(es): 3  
14.4. Packing group: II  
 Hazard label: 3+8



Special Provisions: 274  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 EmS: F-E, S-C

**Air transport (ICAO-TI/IATA-DGR)**

14.1. UN number or ID number: UN 2924  
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S.  
14.3. Transport hazard class(es): 3  
14.4. Packing group: II  
 Hazard label: 3+8



Special Provisions: A3  
 Limited quantity Passenger: 0.5 L  
 Passenger LQ: Y340  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 352  
 IATA-max. quantity - Passenger: 1 L  
 IATA-packing instructions - Cargo: 363  
 IATA-max. quantity - Cargo: 5 L

**Safety Data Sheet**

according to UK REACH Regulation

**Ceramic Coating**

Revision date: 17.05.2022

Product code: 359500018

Page 14 of 15

**14.6. Special precautions for user**

No information available.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48, Entry 75

2010/75/EU (VOC): 60,1 % (558,93 g/l)

2004/42/EC (VOC): 60,1 % (558,93 g/l)

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Abbreviations and acronyms**

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

VOC: Volatile Organic Compounds

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

## Safety Data Sheet

according to UK REACH Regulation

### Ceramic Coating

Revision date: 17.05.2022

Product code: 359500018

Page 15 of 15

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 4; H302	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*