DirectTex®
Eco-Beach Jersey

Fields of application

.02 .04 .05 .06 .07

Specifications

REF. 599094 141

100 % polyester
knit fabrics
PVC-free, recyclable

ca. 160/ 252/ 320/ 505 cm
ca. 63/ 99/ 126/ 199 inch
other widths available on request

B-s1, d0 DIN EN 13501-1

ca. 95 g/m²
ca. 2.8 oz/yd²

ca. 0.29 mm
ca. 290 µm

rolls
50/ 100 m
55/ 109 yd

Air > 3000 mm/s
DIN EN 9237

length: 249 N
cross: 260 N
DIN EN ISO 13934-1

length: 50 %
cross: 90 %
DIN EN 53859-5

Specs UV stable

cold, heat, ultrasonic cut

Printing methods

print	UV	Latex	Dyesub
Inside	•		•
Outside			

Article shrinkage
(50 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	1,0 %	1,4 %	•
190°C	1,1 %	2,0 %	
200°C	1,2 %	2,5 %	
210°C	1,5 %	2,9 %	

Certifications

OEKO TEX® STANDARD 100 09.0.67573 Hohenstein HTTI

PONGS GROUP GMBH & CO. KG
Bahnhofstraße 21
07919 Pausa-Mühltroff
Germany
Phone +49 36645 350-0
salestt@pongs.de
www.pongs.com

Find the latest version by scanning the QR code.
We reserve the right for technical modifications.
The above mentioned details are non-binding.
A tolerance of ± 5% is valid. Effective: 2024/03

DirectTex®
Eco-Beach Jersey

Fields of application

.02 .04 .05 .06 .07

Ref.-Nr.: 599094 141 | Preview print sample

PONGS GROUP GMBH & CO. KG
Bahnhofstraße 21
07919 Pausa-Mühltroff
Germany
Phone +49 36645 350-0
salestt@pongs.de
www.pongs.com

Find the latest version by scanning the QR code.
We reserve the right for technical modifications.
The above mentioned details are non-binding.
A tolerance of ± 5% is valid. Effective: 2024/03