

PRODUCT DESCRIPTION

Issue# 0820

4776RLA Conform Series[®] application tape consists of a premium grade, heavily saturated paper with high tack adhesion. Designed to aid the transfer and installation of small and large graphics, 4776RLA protects graphics printed with UV screen print inks and clear coats. Its high tack rubber adhesive is specially formulated to flow into the peaks and valleys of the textured surface of four color prints. 4776RLA features RLA[®] technology with improved adhesion to paper or film release liners.

Adhesive	Rubber-based
Color	White/Translucent
Thickness tape	127 microns
Thickness tape + adhesive	155 microns
Adhesion to steel*	19-21 N/100mm
Tensile	332 N/100mm
Elongation	12%
Tear resistance	70-80 grams
Shelf life**	1 year

* Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture

** Stored at 22°C / 50-55% RH

FEATURES & BENEFITS

- Heavyweight paper prespacing tape with a high tack adhesive.
- No adhesion build to store graphics.
- Extra-heavy weight facestock makes handling of large graphics easier. Heavier paper is also less likely to tear during removal, so installations are completed with fewer delays.
- Alternative to 3M SCPS-2 and ABI 792U.
- Conform[®] Release Liner Adhesion (RLA) prevents tunneling and edge curl.
- Removes easily following graphics application.
- If adhesive touches adhesive, 4776RLA pulls apart easily with no adhesive delamination.
- Works well in either wet or dry applications with no adhesive transfer.

APPLICATIONS

- Protective premask for graphics printed with UV inks and clear coats.
- Excellent surface protection for stored screen printed graphics.

Important notice: All RTape products are subject to continuous quality control throughout the manufacturing process and are warranted to be free from manufacturing defects. RTape stands behind its products and will replace or credit any defective material. Because RTape products are used for a variety of applications, the purchaser is responsible for determining the suitability and performance of this product for their specific purpose, prior to use and the purchaser shall assume all risks regarding such use.

Nekoosa - RTape Corp.
6 Ingersoll Road, South Plainfield, NJ 07080
Tel: 908-753-5570 Fax: 908-753-5014
sales@rtape.com
www.rtape.com

Represented in Europe by:
the iC GROUP
Industriezone Langevoorde,
Groendreef 35, 9880 Aalter, Belgium
Tel: +32 9 216 67 00
info@theicgroup.eu
www.theicgroup.eu