

## PRODUCT DESCRIPTION

Issue# 0720

**AT65** Clear Choice Series<sup>®</sup> features a polypropylene film with excellent clarity, abrasion resistance and lay flat characteristics. Its acrylic adhesive is designed for clean pick up and transfer performance on all brands of cast or calendered vinyl. The stable adhesive will not build in tack level when applied to vinyl graphics for extended periods of storage, therefore transfer is never a problem. AT65's new universal adhesive system is optimized to transfer the widest variety of pressure-sensitive vinyl films.

Adhesive	Modified polyacrylate
Color	Clear polypropylene
Thickness tape	93 microns
Thickness tape + adhesive	108 microns
Adhesion to steel*	1-2 N/25mm
Tensile	3600 psi (25 MPa)
Elongation	750%
Shelf life**	1 year

\* Adhesion PSTC-101, 1 minute on stainless steel at time of manufacture

\*\* Stored at 22°C / 50-55% RH

## FEATURES & BENEFITS

- Excellent for wet application installation of gloss/smooth cut graphics; small to medium size.
- Universal high tack film for most sign applications.
- Well suited for transferring small computer cut copy films with fine detail.
- Static control for easier handling.
- Exceptional lay flat resists tunneling and edge curl on liners.
- Works well in wet applications with no adhesive residue.
- Superior clarity aids registration of multiple color overlays.
- Recommended for transferring vinyl films utilizing liners with tighter release.

## APPLICATIONS

- Universal application tape for wet and dry applications
- Small-Medium sized with high detail die-cut graphics.
- Vinyl films with tight liner release.
- Multiple color graphic overlays.

**Important notice:** All RTape products are subject to continuous quality control throughout the manufacturing process and are warranted to be free from manufacturing defects. RTape stands behind its products and will replace or credit any defective material. Because RTape products are used for a variety of applications, the purchaser is responsible for determining the suitability and performance of this product for their specific purpose, prior to use and the purchaser shall assume all risks regarding such use.

**RTape Corp.**  
6 Ingersoll Road, South Plainfield, NJ 07080  
Tel: 908-753-5570 Fax: 908-753-5014  
sales@rtape.com  
[www.rtape.com](http://www.rtape.com)

Represented in Europe by:  
**the iC GROUP**  
Industriezone Langevoorde,  
Groendreef 35, 9880 Aalter, Belgium  
Tel: +32 9 216 67 00  
[info@theicgroup.eu](mailto:info@theicgroup.eu)  
[www.theicgroup.eu](http://www.theicgroup.eu)