Multi-Solvent HQ Poster WhiteBack SG

Highlights

>>> High stiffness and strength

>>> High color saturation saves up to 30% ink

>>> Water-repellent surface

	Technical specifications
Material	Multi-layer coated, weather and water resistant, bright white paper, specially designed for solvent inks or UV-curing inks.
Color	White, satin finish
Total basis weight	195 g/m² (ISO 536)
Total thickness	210 µm (ISO 534) 8.3 mil (ISO 534)
Farbort (D50/2°)	L: 94.3 (ISO 13655, M0) a: 1.3 (ISO 13655, M0) b: -4.4 (ISO 13655, M0)
opacity	> 98 % (ISO 2471)
scope	- High-quality photo reproductions - Signs for indoor and outdoor use - Poster advertising, general outdoor advertising - Indoor advertising - City light posters / lightbox displays outdoors.
Characteristics	"Multi-Solvent HQ Poster WhiteBack SG" is suitable for outdoor poster advertising and shows very good scratch and fold resistance without white breakage. Furthermore, "Multi-Solvent HQ Poster WhiteBack SG" has the following advantages: - Water-repellent surface - Photorealistic posters - High stiffness and strength - High color saturation saves up to 30% ink. - Ideally suited for eco-solvent inks

IGEPA

Multi-Solvent HQ Poster WhiteBack SG

	Technical specifications
Processing instructions / Storage	- Please note that when using an HP Latex 300 series printer, print roll by roll! - The amount of ink used must be adjusted to the paper. Both the individual colors cyan, magenta, yellow, and black (ink restrictions) and the total amount of ink should be reduced. Both the reduction of individual colors and the Total ink content has a positive influence on drying properties and ink costs. - In general, the recommendations of the printer and ink manufacturers should be followed. The settings to be adjusted on the printer Temperatures for media preheating or from the drying unit must be subjected to prior testing, as these are highly dependent on the printer type. - Posting: The paper should be kept moist for a sufficient amount of time (e.g., in a poster box). We recommend at least eight hours. A longer soaking time will not negatively affect the paper. The user is responsible for taking the appropriate microbiological precautions. When mounted on a billboard, the paper will last for 3 months without lamination. Lamination is recommended if the paper is exposed to harsh environmental conditions or if a longer display period is planned. Protecting the edges and corners is advisable if the billboard area is cleaned regularly. - To ensure the product properties, the product should be stored and used at 30 - 65% relative humidity and at 10 - 30 °C (50- 86 °F). - Sufficient water resistance is not guaranteed when used in combination with latex/IR inks.
Dimensions	106,7 cm x 50 m (SSQ-MSHQPWSGR106-50) 137,2 cm x 50 m (SSQ-MSHQPWSGR137-50) 152,4 cm x 50 m (SSQ-MSHQPWSGR152-50)

This information reflects the current state of our knowledge and is intended to provide non-binding information about the products and their possible applications. No legally binding guarantee of specific properties can be derived from this information. All information is provided without warranty. Last updated: April 2016

IGEPA